PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

H04M 3/00, 11/00, H04L 12/64

A1

(11) International Publication Number: WO 97/39560

(43) International Publication Date: 23 October 1997 (23.10.97)

(21) International Application Number: PCT/CA97/00128

(22) International Filing Date: 26 February 1997 (26.02.97)

(30) Priority Data: 08/631,162 12 April 1996 (12.04.96) US

(71) Applicant: NORTHERN TELECOM LIMITED [CA/CA]; World Trade Center of Montreal, 8th floor, 380 St. Antoine Street West, Montreal, Quebec H2Y 3Y4 (CA).


(72) Inventors: HENRY, Robert, V.; 4016 Crown Hill Drive, Durham, NC 27707 (US). KENEDI, Robert; 11726 Night Heron Drive, Naples, FL 34119-8888 (US).

(74) Agent: TOYOOKA, Yoshiharu; Northern Telecom Limited, Patent Dept., P.O. Box 3511, Station "C", Ottawa, Ontario K1Y 4H7 (CA). (81) Designated States: AU, CA, CN, JP, KR, MX, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: TERMINATING DATA VOICE CALL ARCHITECTURE



(57) Abstract

The invention resides in the field of telecommunication network architecture which supports voice connections over data networks and publicly switched networks. In one preferred embodiment, the invention permits a voice connection between a personal computer or CPE device (10) and a plain regular telephone terminal (30), over an Internet or data network (20) and a local exchange carrier or local access provider of the PSTN (24) to which the regular telephone terminal is connected.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LŤ	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Тово
BB	Barbados	GH	Ghana	MG	Madagescer	ŢJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Стессе	•	Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Besin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	LS	Iceland	MW	Malawi	US	United States of Americ
CA.	Canada	IТ	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
ÇG.	Congo	KE	Кепуа	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan .	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KР	Democratic People's	NZ	New Zealand		
CM.	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ.	Kazakatan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonis	LR	Liberia	SG	Singapore		

TERMINATING DATA VOICE CALL ARCHITECTURE

Technical Field and Industrial Application

The invention generally relates to voice services over computer and/or data networks. In particular, it is directed to a service architecture by which a duplex voice call connection can be established between a computer or CPE (customer premise equipment) device and a regular telephone over wide area data networks, such as Internet, which are mainly designed for connection among computers.

10

15

20

25

30

35

Background of Invention

Software packages for voice communications over the Internet are now generally available for personal computers (PCs). Widespread use of the Internet voice communications packages are severely inhibited because terminating access at any point in time is only available to users who happen to be actively on the "Network" (Internet) at the time of the call, and are also equipped with compatible software. Alternatively, the call may be pre-arranged via Internet mail or regular telephone communications. A product has also been introduced which allows the caller to leave Internet voice messages through a PBX or key system, making it as easy to retrieve messages as using a plain telephone. Users can leave voice messages and retrieve messages using the Internet and associated PBX device. The previously mentioned Internet voice messaging product uses a store and forward process unlike the present invention being presented here, which uses a live network architecture connection. The present invention allows an Internet voice call or other data voice call to be terminated at a local exchange carrier (LEC) or local access provider (LAP) so that a live voice connection can be established between a PC and a plain regular telephone. Due to lack of an accepted term, this service is hereinafter called Terminating Internet Voice Call Service, or TIVC. While this specification prominently mentions "Internet", the architecture according to the invention is equally applicable to any data network. It should also be noted that in the field of telephony, "terminating a call" involves several consequential steps which are performed at a terminating LEC or LAP, such as generating a ring signal, generating a

15

20

25

30

35

busy signal, responding to a receiver going off-hook, etc., so that a proper telephone connection is established between two parties.

There are a few problems which hinder widespread use of the TIVC service. These include terminating access ("reach") limited to those who are compatibly equipped with hardware and software and are ready to receive the call; there is also no alerting mechanism for those who are inactive/disconnected from the Internet or data network (even though equipped); and there is no way to place an Internet voice call to someone with plain old telephone service (POTS) anywhere in the world.

The TIVC service would be a significant growth enabler for voice traffic on Internet or other data networks in that it eliminates the three major growth inhibiting problems stated above. At the same time, the TIVC service also offers a new terminating access service opportunity to LEC's (local exchange carriers) and LAPs (local access providers), consequently increasing network traffic and service revenues. As a result of the TIVC invention the number of reachable parties for a caller expands from the current limitation of only those who are equipped and active on the Internet or data network at the time the call is being placed, to all global telephone subscribers (or their answering system) at any time.

Objects of Invention

It is therefore an object of the invention to provide a network architecture which supports the termination of data voice traffic at a local exchange carrier (LEC) or local access provider (LAP) of the public switched telephone network (PSTN).

It is another object of the invention to provide a method of terminating data voice traffic emerging from a data network at a local exchange carrier of the PSTN.

It is yet a further object of the invention to provide a network architecture in which a telephone number is converted to the data address of a serving data access system such as the Internet Access System (IAS) using a data addressing system and a telephone number conversion process.

Disclosure of the Invention

Briefly stated, the invention is directed to a method of handling a data voice call set up request for the purpose of establishing a duplex voice connection between an originating CPE and a telephone 5 terminal. The method comprises steps of responding to the voice call set up request at a translation server connected to a data network, and translating the telephone number of the telephone terminal to the data address of a data network access system. There is a further step of the data network access system responding to the originating CPE with a voice signal output.

According to another aspect, the invention is directed to a method of routing and terminating a data voice call at a local exchange carrier or local access provider from which a voice connection can be made to a regular telephone terminal to which the data voice call is destined. The method comprises steps of receiving a data voice call request and converting the data voice call request to a voice signal output. The method further includes steps of routing the voice signal output to a central switching office of the local exchange carrier or local access provider, and ringing the regular telephone terminal in response to the voice signal output.

According to yet another aspect, the invention relates to a method of establishing a duplex voice connection between an originating CPE and a called telephone terminal. The method comprises steps of the originating CPE sending a data voice call request to a data network and in response to the data voice call request, the data network sending the originating CPE a data or IP address and connection information of a data network access system connected to the data network. The method further includes steps of the originating CPE sending a data voice call to the data network access system at its data or IP address and the data network access system converting the data voice call to a voice signal output. There are further steps of routing the voice signal output to a central switching office to which the called telephone terminal has access, and the central switching office sending a ring signal to the called telephone terminal.

10

15

20

25

30

10

15

20

25

30

35

Brief Description of the Drawings

Figure 1 shows schematically a network architecture according to one embodiment of the invention; and

Figures 2-4 show schematically various steps to carry out a method according to embodiments of the invention.

Mode(s) of Carrying Out the Invention

The Terminating Internet Voice Call Service, hereinafter called TIVC, is a new service which would be offered by LEC's and LAP's, enabling their customers to receive voice calls which were originated from the Internet or data network users using a computer or CPE Internet voice communication package. In one embodiment it involves Internet because it is the most widely accepted data network but it should be emphasized that the invention can be implemented using any data network.

The invention defines a new service, new method, and new architecture, which will allow an Internet or data voice caller to originate and establish a two-way voice connection using the Internet or data network, and the PSTN from a PC (personal computer) or other CPE device, terminating to a plain telephone anywhere in the world. This terminating service will generate new revenue for the LEC/LAP service providers.

The TIVC service will allow LEC/LAP to minimize lost revenue from pure Internet PC to PC voice calling, and expand the terminating reach for Internet voice callers to existing plain telephone subscribers around the world.

Figure 1 shows a network architecture according to one embodiment of the invention. It should be noted that the description that follows is only about one embodiment of the invention and there are many possible implementations to realize the inventive idea without departing from the spirit of the invention. In the figure, a PC/CPE 10 is connected to the PSTN 12 via a modem 14. The computer is equipped with a voice card or such capability so that a telephone set or microphone and speaker configuration (multi-media package) 16 or any other CPE device can be connected for voice call. An Internet access provider (IAP) 18 provides access to the PSTN connection and to the Internet 20. According to this embodiment, a server called a TIVC

10

15

20

25

30

35

server 22 (Terminating Internet Voice Call Server) provides database services of address tables containing telephone numbers, data routing information, TCP/IP addresses, etc. At a local exchange carrier 24 of the PSTN near the called party telephone set, an entity called IAS 26 (Internet Access System) enables the bridging between data voice call traffic from the Internet and ordinary telephone voice call traffic in the local exchange carrier containing CO equipment 28 and a plain old telephone (POTS) or other telephone set 30 of a standard telephone subscriber connected to it.

The accompanying Figures 2-4 schematically illustrate some typical steps of establishing voice call traffic between a PC/CPE device and an ordinary telephone set connected to a central switching office (CO) of a local exchange carrier in the embodiment described above in connection with Figure 1.

In Figure 2, a data voice call to a POTS is initiated at the PC/CPE by dialing or inputting a called party's PSTN telephone number. The PC/CPE is equipped with a voice card for digitizing voice. As shown by 40, through application software, the PC or CPE device launches a translation query into the Internet by way of the IAP for conversion of the PSTN telephone number to data or the IP address of an IAS using a TIVC number identifier translation. The TIVC server receives the query and checks its database at 42 for conversion of the PSTN telephone number to the Internet address of the IAS, which has the capability of terminating voice call, and routing it to the called party's CO. At 44, the TIVC server responds back to the originating PC/CPE with the terminating telephone number data or IP IAS address for terminating the TIVC call.

In Figure 3, the PC/CPE device receives a response from the TIVC server concerning the data or TCP/IP address at 50, and launches a connection request 52 to the terminating IAS with the telephone number to be connected at the CO. The terminating IAS receives the connection request at 54 and the PC/CPE application sets up the Internet data/voice connection to the terminating office destination IAS data or IP address with an enclosed terminating call identifier. The terminating IAS generates a standard outgoing call to CO equipment at 56 using a trunk or local line so that a two-way voice connection is made between the CO equipment and the originating PC/CPE device.

10

15

20

35

The central office system would then ring the standard POTS telephone through normal switching technologies. When the answering party answers the call, the complete two-way (duplex) voice path would be established to the originating PC /CPE device.

In Figure 4, end-to-end two-way voice connection is established between the originating PC/CPE device on the Internet and a POTS telephone on the PSTN. The terminating IAS receives the incoming call from the Internet as a data call and converts it to voice output to be routed to a standard trunk or local line of the CO equipment.

In one implementation, billing can be handled by the receiving IAS system using Internet, an industry accepted cash system, as required for terminating LD (Long Distance) charges, if required by the TIVC call originator.

It should be noted that the implementation architecture described above is one of many possible embodiments. For example, the invention can be implemented in various different ways as follows:

- a) Use of AIN (Advanced Intelligent Network) capability, whereby the IAS (Internet Access System) could interface with an AIN database to perform the telephone number to terminating data/IP address conversion and respond to the originating caller system with the terminating calling information. This implementation would be an alternative to having the conversion database co-located with the IAS system.
- The IAS system would not have to be a separate system from the Central Office switch, but this functionality could be built into the actual Central Office switching system. The software and Central Processing Unit (CPU) could be built into the CO switch. Again, the conversion of telephone number to terminating data/IP address could be accomplished with a built-in database, or Advanced Intelligent Network (AIN) capabilities could be used to perform the translation.
 - c) In addition to scenarios (a) and (b) described above for the telephone number to data or IP system translation, the Central Office switch could have built-in capability to actually "route" the TIVC call to the appropriate telephone line or trunk for termination.

WHAT IS CLAIMED IS:

10

15

20

25

35

1. A method of handling a data voice call set up request for the purpose of establishing a duplex voice connection between an originating CPE and a telephone terminal, comprising steps of:

responding to the voice call set up request at a translation server connected to a data network;

translating the telephone number of the telephone terminal to the data address of a data network access system;

the data network access system responding to the originating CPE with a voice signal output.

2. A method of terminating a data voice call at a local exchange carrier or local access provider from which a voice connection can be made to a regular telephone terminal to which said data voice call is destined, comprising steps of:

receiving a data voice call request;

converting the data voice call request to a voice signal output; routing the voice signal output to a central switching office of the local exchange carrier or local access provider; and

ringing the regular telephone terminal in response to the voice signal output.

3. A method of establishing a duplex voice connection between an originating CPE and a called telephone terminal, comprising steps of:

the originating CPE sending a data voice call request to a data network;

in response to the data voice call request, the data network sending the originating CPE a data or IP address and connection information of a data network access system connected to the data network;

the originating CPE sending a data voice call to the data network access system at its data or IP address;


the data network access system converting the data voice call to a voice signal output;


routing the voice signal output to a central switching office to which the called telephone terminal has access; and


10


the central switching office sending a ring signal to the called telephone terminal.

- 4. The method according to claim 3 wherein the CPE is a data terminal such as a computer which is equipped with voice capability.
 - 5. The method according to claim 4, wherein the step of the data network sending the originating CPE a data or IP address of a data access system comprises a further step of a server connected to the data network searching a database.
 - 6. The method according to claim 5 wherein the data voice call request is based on a telephone number of a called telephone terminal.
- 7. The method according to claim 6 wherein the data voice signal output is an industry standard outgoing call signal.









INTERNATIONAL SEARCH REPORT

Inte. unal Application No PCT/CA 97/00128

CLASSIFICATION OF SUBJECT MATTER ÎPC 6 H04M11/00 H04L12/64 H04M3/00 According to International Patent Classification (IPC) or to both national classification and IPC **B. FIELDS SEARCHED** Minimum documentation searched (classification system followed by diastrication symbols) IPC 6 HO4M Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevant passages Relevant to claim No. US 5 610 910 A (FOCSANEANU MIHAI ET AL) 1 Ε 11 March 1997 see column 7, line 51 - column 8, line 58 see figure 8 2-4 P,X US 5 604 737 A (IWAMI NAOKO ET AL) 18 February 1997 6.7 Α see abstract see column 13, line 19 - column 18, line see figures 1,9,11 Α 1-7 vol. 21, no. 2, 1 February 1996, page 83/84, 86, 88 XP000566097 "DIAL 1-800-INTERNET WITH NEW MULLER N: SOFTWARE, YOU CAN TALK BUSINESS OVER THE NET AND AVOID LONG-DISTANCE CHARGES" Further documents are listed in the continuation of box C. Patent family members are listed in annex. X I Special categories of cited documents: "T" later document published after the international filing date or priority date and not in conflict with the application but 'A' document defining the general state of the art which is not considered to be of particular relevance. cited to understand the principle or theory underlying the earlier document but published on or after the international "X" document of particular relevance; the claimed invention filing date cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the "O" document referring to an oral disclosure, use, exhibition or document is combined with one or more other such docu-ments, such combination being obvious to a person stelled other means in the art. document published prior to the international filing date but later than the priority date claimed '&' document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report 0 9, 06, 97 23 May 1997 Name and mailing address of the ISA Authorized officer European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Ripswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Megalou, M Fax: (+31-70) 340-3016

1

INTERNATIONAL SEARCH REPORT

Inte onal Application No PCT/CA 97/00128

	uon) DOCUMENTS CONSIDERED TO BE RELEVANT	Palament to alarm No.					
tegory *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.					
	IEEE SPECTRUM, vol. 33, no. 1, 1 January 1996, pages 30-41, XP000566101 "COMMUNICATIONS"						
\	WO 92 22976 A (TELENOKIA OY) 23 December 1992						
P,A	WO 96 20553 A (ALPHANET TELECOM INC) 4 July 1996 see claims 11-20	1 - 7					
	•••••						
τ							
,							

-INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/CA 97/00128

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5610910 A	11-03-97	WO 9707625 A	27-02-97
US 5604737 A	18-02-97	JP 7170288 A	04-07-95
WO 9222976 A	23-12-92	FI 91203 C AU 652258 B AU 1878392 A EP 0543996 A JP 6500452 T US 5450472 A	25-05-94 18-08-94 12-01-93 02-06-93 13-01-94 12-09-95
WO 9620553 A	04-07-96	CA 2139081 A AU 4294996 A US 5608786 A	24-06-96 19-07-96 04-03-97

This Page Blank (uspto)